




1217M0259

Grès cérame Zoza Blanc 300x600x9.5 (298x598) c

oloré dans la masse, rectifié - R10 B - V2 - 1.08 m² - 21.85 kg/ m² - 50,40 m²/palette

ENSAYOS/ TESTS		RESULTADOS/ RESULTS	
	UNE-EN ISO 10545-2 DIMENSIONES Y ASPECTO SUPERFICIAL UNE-EN ISO 10545-2 DIMENSIONS AND SURFACE QUALITY	DIMENSIONES DIMENSIONS	CUMPLE CON LA NORMA COMPLIES WITH THE STANDARD
	UNE-EN ISO 10545-3 ABSORCIÓN DE AGUA UNE-EN ISO 10545-3 WATER ABSORPTION	VALOR MEDIO (%) AVERAGE VALUE (%)	≤ 0,5 %
	UNE-EN ISO 10545-4 RESISTENCIA A LA FLEXIÓN UNE-EN ISO 10545-4 MODULUS OF RUPTURE	FUERZA DE ROTURA BREAKING STRENGTH (N)	1600 - 2400 N
		RESISTENCIA A LA FLEXIÓN MODULUS OF RUPTURE (N/mm ²)	35 – 45 N/mm ²
	UNE-EN ISO 10545-9 RESISTENCIA AL CHOQUE TÉRMICO UNE-EN ISO 10545-9 THERMAL RESISTANCE	RESULTADO RESULT	RESISTE RESISTS
	UNE-EN-ISO 10545-11 RESISTENCIA AL CUARTEO UNE-EN-ISO 10545-11 CRAZING RESISTANCE	RESULTADO RESULT	RESISTE RESISTS
	UNE-EN ISO 10545-12 RESISTENCIA A LA HELADA UNE-EN ISO 10545-12 FROST RESISTANCE	RESULTADO RESULT	RESISTE RESISTS
	UNE-EN ISO 10545-13 RESISTENCIA QUÍMICA UNE-EN ISO 10545-13 CHEMICAL RESISTANCE	CLORURO AMÓNICO AMMONIUM CHLORIDE 100 g/l	A
		HIPOCLORITO SÓDICO SODIUM HYPOCHLORITE 20 mg/l	A
		ÁCIDO CLORHÍDRICO HYDROCHLORIC ACID 3%	CUMPLE CON LA NORMA COMPLIES WITH THE STANDARD
		ÁCIDO CÍTRICO CITRIC ACID 100 g/l	
		HIDRÓXIDO POTÁSICO POTASSIUM HYDROXYDE 30 g/l	
	UNE-EN ISO 10545-14 RESISTENCIA A LAS MANCHAS UNE-EN ISO 10545-14 STAIN RESISTANCE	ÓXIDO VERDE EN ACEITE LIGERO GREEN AGENT IN LIGHT OIL	5
		SOLUCIÓN ALCOHÓLICA DE YODO IODINE SOLUTION IN ALCOHOL	5
		ACEITE DE OLIVA OLIVE OIL	5
	DIN 51130 ÁNGULO CRÍTICO DE DESLIZAMIENTO (RAMPA) DIN 51130 CRITICAL ANGLE OF SLIP (INCLINED PLATFORM)	RESULTADO RESULT	R10
	UNE-EN-ISO 10545-7 ABRASIÓN SUPERFICIAL (PEI) UNE-EN-ISO 10545-7 SURFACE ABRASION (PEI)	RESULTADO RESULT	PEI 3

OBSERVACIONES:

VºBº LABORATORIO:

GlobalEPD
A VERIFIED ENVIRONMENTAL DECLARATION



Este producto contribuye a satisfacer créditos bajo
This product contributes toward satisfying credits under

LEED®

